



Turning Light into Savings ▶▶▶



TUBE AC120-277V

9W,10W,14W,15W,40W,43W

Integrated Driver T8 Tubes for direct wire installation to replace T8 and T12 Fluorescent Tubes.

Designed to be noise-free and non flickering, our tubes selection from 9 watt to 43 watt which replaces up to 110 watt T8 Fluorescent, saving up to 60% in energy.

Excellent color consistency, with the option of Plastic/Aluminum Construction or Glass Construction. Our integrated driver design brings you the best retrofit solution.

Key Features & Benefits

- ▶ Retrofit for T8 & T12 Fluorescent Tube
- ▶ Excellent color consistency
- ▶ No flickering
- ▶ Noise-free design
- ▶ Universal Voltage 120-277V
- ▶ UL/cUL Listed
- ▶ Operating Temperature: -4°F to 113°F
- ▶ 50,000 hrs rated average life

Applications

- ▶ Conference Room
- ▶ Meeting Room
- ▶ Factory/ Office
- ▶ School & University
- ▶ Hospital
- ▶ Hotel

Color Choices




White


Qualifications




Plastic/Aluminum Tube

Item Code	Description	Color Temp	Wattage	Lumen Output	Equivalent Wattage	Length	Base	CRI	Beam Angle	Rated Hours	
5778	LED10T8/24FR10/840	4000K	10	1,109	25	2-ft/ 24"	Bi-Pin	>80	120°	50,000	•
5774	LED10T8/24FR10/850	5000K	10	1,109	25	2-ft/ 24"	Bi-Pin	>80	120°	50,000	•
5779	LED10T8/36FR10/840	4000K	10	1,000	25	3-ft/ 36"	Bi-Pin	>80	120°	50,000	
5817	LED14T8/FR17/840	4000K	14	1,700	32	4-ft/ 48"	Bi-Pin	>80	120°	50,000	•
5818	LED14T8/FR17/850	5000K	14	1,700	32	4-ft/ 48"	Bi-Pin	>80	120°	50,000	•
5811	LED40T8/96FR43/840	4000K	40	4,300	75	8-ft/ 96"	Single	>80	120°	50,000	

Glass Tube

Item Code	Description	Color Temp	Wattage	Lumen Output	Equivalent Wattage	Length	Base	CRI	Beam Angle	Rated Hours	
5951	LED9T8/24FR10/840	4000K	9W	1,000	17	2-ft/ 24"	Bi-Pin	>80	325°	50,000	•
5952	LED9T8/24FR10/850	5000K	9W	1,000	17	2-ft/ 24"	Bi-Pin	>80	325°	50,000	•
5953	LED15T8/36FR16/840	4000K	15W	1,600	25	3-ft/ 36"	Bi-Pin	>80	325°	50,000	
5954	LED15T8/36FR16/850	5000K	15W	1,600	25	3-ft/ 36"	Bi-Pin	>80	325°	50,000	
5955	LED15T8/FR18/840	4000K	15W	1,800	32	4-ft/ 48"	Bi-Pin	>80	325°	50,000	•
5956	LED15T8/FR18/850	5000K	15W	1,800	32	4-ft/ 48"	Bi-Pin	>80	325°	50,000	•
5958	LED43T8/96FR55/840	4000K	43W	5,500	110	8-ft/ 96"	Single	>80	325°	50,000	
5959	LED43T8/96FR55/850	5000K	43W	5,500	110	8-ft/ 96"	Single	>80	325°	50,000	
5960	LED43T8/96FR55/R17D/840	4000K	43W	5,500	110	8-ft/ 96"	R17d	>80	325°	50,000	
5961	LED43T8/96FR55/R17D/850	5000K	43W	5,500	110	8-ft/ 96"	R17d	>80	325°	50,000	

► Dimensions

	Item	A	B		Weight (lbs)
	2-ft	1.00-in	24.00-in		0.50
	3-ft	1.00-in	36.00-in		0.50
	4-ft	1.00-in	48.00-in		0.80
	8-ft	1.00-in	96.00-in		1.50

► Master Carton Package

